

# QDLASER

## QLF063A /QLF063D

660 nm 100mW FP LASER TO-CAN

C00100-01 January 2013



### 1. DESCRIPTION

The QLF063A/QLF063D are 660 nm quantum well laser devices designed for high output power application. The laser diode is mounted into a TO-56 header including a monitor PD and hermetic sealed with a flat glass cap.

### 2. FEATURES

- 660 nm FP-LD
- $\Phi$ 5.6mm TO-CAN package
- High output power of 100mW and high slope efficiency
- Including monitor PD
- Two types of pin assignments: anode common type (QLF063A)/cathode common type (QLF063D)

### 3. APPLICATIONS

- Industrial laser markers
- Measuring instruments
- Life science applications

### 4. ABSOLUTE MAXIMUM RATING

(CW operation,  $T_c = 25^\circ\text{C}$ , unless otherwise specified)

| PARAMETER             | SYMBOL    | RATING    | UNIT             |
|-----------------------|-----------|-----------|------------------|
| Optical output power  | $P_o$     | 130       | mW               |
| LD reverse voltage    | $V_{RLD}$ | 2         | V                |
| PD reverse voltage    | $V_{RPD}$ | 30        | V                |
| Operation temperature | $T_c$     | -10 to 60 | $^\circ\text{C}$ |
| Storage temperature   | $T_{stg}$ | -40 to 85 | $^\circ\text{C}$ |

distributed by









Ohmstrasse 4  
85716 Unterschleissheim  
[www.imm-photonics.de](http://www.imm-photonics.de)





Tel.: +49 89 3214120  
Fax.: +49 89 32141211  
[sales@imm-photonics.de](mailto:sales@imm-photonics.de)

## 5. OPTICAL AND ELECTRICAL CHARACTERISTICS

( $T_c = 25^\circ\text{C}$ , unless otherwise specified)

| PARAMETER                    | SYMBOL      | TEST CONDITION                                   | MIN | TYP | MAX | UNIT          |
|------------------------------|-------------|--|-----|-----|-----|---------------|
| Threshold current            | $I_{th}$    | CW   | -   | 55  | 70  | mA            |
| Operation current            | $I_{op}$    | CW, $P_o=100\text{ mW}$                          | -   | 145 | 200 | mA            |
| Operation voltage            | $V_{op}$    | CW, $P_o=100\text{ mW}$                          | -   | 2.5 | 3.0 | V             |
| Slope efficiency             | $\eta$      | CW, $P_o=5 - 100\text{ mW}$                      | 0.8 | 1.1 | -   | W/A           |
| Monitor current              | $I_m$       | CW, $P_o=100\text{ mW}$ ,<br>$V_{RD}=5\text{ V}$ | 50  | 280 | 600 | $\mu\text{A}$ |
| Peak wavelength              | $\lambda_p$ | CW, $P_o=100\text{ mW}$                          | 655 | 660 | 665 | Nm            |
| Far filed pattern horizontal | $\theta_h$  | CW, $P_o=100\text{ mW}$                          | 7   | 10  | 13  | deg.          |
| Far filed pattern vertical   | $\theta_v$  | CW, $P_o=100\text{ mW}$                          | 11  | 14  | 17  | deg.          |
| Beam angle Horizontal        | $d\theta_h$ | CW, $P_o=100\text{ mW}$                          | -3  | -   | 3   | deg.          |
| Beam angle vertical          | $d\theta_v$ | CW, $P_o=100\text{ mW}$                          | -3  | -   | 3   | deg.          |






distributed by



Ohmstrasse 4  
85716 Unterschleissheim  
[www.imm-photonics.de](http://www.imm-photonics.de)

Tel.: +49 89 3214120  
Fax.: +49 89 32141211  
[sales@imm-photonics.de](mailto:sales@imm-photonics.de)

## 6. OUTLINE DRAWINGS



## 7. NOTICE

- Safety Information

This product is classified as Class 3B laser product, and complies with 21 CFR Part 1040.10.

Please do not take a look laser lighting in operations since laser devices may cause troubles to human eyes.

Please do not eat, burn, break and make chemical process of the products since they contain GaAs material.

- Handling products

Semiconductor lasers are easily damaged by external stress such as excess temperature and ESD.

Please pay attention to handling products, and use within range of maximum ratings.

QD Laser takes no responsibility for any failure or unusual operation resulting from improper handling, or unusual physical or electrical stress.

- RoHS

This product conforms to RoHS compliance related EU Directive 2002/95/EC.

QD Laser, Inc.

Contact : [info@qdlaser.com](mailto:info@qdlaser.com) <http://www.qdlaser.com>

Copyright 2013 All Rights Reserved by QD Laser, Inc.

Keihin Bldg. 1F 1-1 Minamiwatarida-cho, Kawasaki-ku, Kawasaki, Kanagawa Zip 210-0855 Japan

All company or product names mentioned herein are trademarks or registered trademarks of their respective owners. Information provided in this data sheet is accurate at time of publication and is subject to change without advance notice.