

FIBERPOINT® adapter



2.50 to 1.25, POF, SMA adapters

The FIBERPOINT® range of fiber fault locators are available with a 2.5 mm universal connector as standard. We offer adapters for 1.25 mm connectors, SMA connectors and POF bare fibers. These allow you to test most common fiber connector types with just one fiber fault locator.

ART.NO.	ADAPTER 2.50 MM TO 1.25 MM 1400000070	ADAPTER FOR POF (POLYMER OPTICAL FIBER) 1400000078	ADAPTER FOR SMA 1400000088
Side of the FIBERPOINT®		2.50 mm SM-ferrule	
Side of the fiber	1.25 mm connection for LC, MU, F3000 etc.	1.5 mm and 2.2 mm	SMA 905 connector
Attenuation		typ. < 1.0 dB	
Weight	10 g	8.5 g	3.5 g

Individual. Innovative. Exceptional.

FIBERPOINT® adapter

APPLICATIONS



Adapter 2.50 mm to 1.25 mm

Adapts 2.50 mm FIBERPOINT® connection to a 1.25 mm connection. Consequently you can check most of the popular fiber connector type with just one fiber optic fault locator.



Adapter for POF

Adapts 2.50 mm FIBERPOINT® connection to a 1.5 mm and 2.2 mm outer diameter polymer optical fiber connection. Consequently you can check both of the popular fiber diameters with one fiber optic fault locator.



Adapter for SMA

Adapts 2.50 mm FIBERPOINT® connection to SMA 905 connection. Consequently you can check both popular fiber connector types with just one fiber optic fault locator.

INCLUDED IN DELIVERY

- Adapter 2.50 mm to 1.25 mm: Dust cap on both sides
- Adapter for POF: Dust cap
- Adapter for SMA: Dust cap
- Plastic foil packaging

NOTES

Compliant with RoHS-requirements (2011/65/EU from June 8, 2011).

The above product specifications are subject to change without notice.

Release 10/2024

Individual. Innovative. Exceptional.

IMM Photonics GmbH | Ohmstraße 4 | 85716 Unterschleißheim | Germany | imm-photonics.de

**WE LOOK
FORWARD**
to solving your
challenge

