

The UV handheld lighting device ilumCURE 1G by IMM Photonics is an UV light source with a central wavelength of 365 nm or 405 nm. It serves as mobile UV light source for the curing of UV adhesives.

The ilumCURE 1G features a robust aluminium housing and was especially developed for fieldwork. The integrated lithium ion battery allows up to 3 hours of continuous operation. The ilumCURE 1G can be re-charged (standard charge) with various USB Ports. With a mains adaptor (separately sold) you can fast charge and / or directly operate the device via an AC power outlet.

Thanks to the high-performance UV LED, the curing of UV adhesives requires only a few seconds of exposure.

WAVELENGTH ART.NO.	365 NM 1600000104	405 NM 1600000105	
UVA Power	330 mW (typ.)	340 mW (typ.)	
Trigger ilumination	Via push-button on housing		
Battery	Li-ion / 3.6 V, 2250 mAh, exchangeable		
Battery safety functions	Over- and undervoltage, overcurrent, excess temperature		
Charging time for completely discharged battery	< 4.0 h fast charge < 5.5 h standard charge		
Operating time with fully charged battery	3.0 hours		
Fast charge	Automatically detected		
Chargers	Fast charge: USB mains adaptor 5 V / 1000 mA Standard charge: various USB mains adaptors, PC		



ilumCURE 1G

WAVELENGTH ART.NO.	365 NM 1600000104	405 NM 1600000105	
Charging indicator (next to USB port)	Orange: Charging in progress Green: Battery is fully charged		
Overall Dimensions	Length 185 mm, max. diameter 27.5 mm		
Lighting tip dimensions	Total length of tip 53 mm, diameter 5 mm (along 8 mm)		
Weight / Material	Approx. 100 g / full metal housing, anodised aluminium		
Operating / storage temperature	+5 °C to +45 °C / -10 °C to +70 °C		
Humidity	5 % to 95 % r. h. (non-condensing)		
Delivery	· ilumCURE 1G	· ilumCURE 1G	
	• Mini USB cable	• Mini USB cable	
	 Instruction manual 	 Instruction manual 	
	· Quadrosafe (L 19 cm, D 4.5 cm, PP, transparent)	· Quadrosafe (L 19 cm, D 4.5 cm, PP, transparent)	
Available accessories	• Fast charge USB mains adaptor (Art. No. 1600000100)	• Fast charge USB mains adaptor (Art. No. 1600000100)	
	 Variable collimating lens W (Art. No. 1600000064) 	 Variable collimating lens W (Art. No. 160000064) 	
	 Variable collimating lens N (Art. No. 1600000071) 	 Variable collimating lens N (Art. No. 1600000071) 	
	• Systainer (Art. No. 1600000114)	• Systainer (Art. No. 1600000114)	

Subject to technical modifications. As per October 2024.

WE LOOK FORWARD to solving your challenge

