
High Power 14-Pin DFB Butterfly Fiber Module

Part Number: 14BF-453



High Power 14-Pin DFB Butterfly Fiber Coupled Module
Single-Mode DFB
Wavelength at 1550nm

Features

- High Output Power
- High Efficiency
- Polarization Maintenance Fiber
- Isolator Included

Application

- LiDAR
- Free Space Communications
- Optical Fiber Communications
- Network Test Equipment

SemiNex delivers the highest available power at infrared wavelengths between 12xx and 19xx nm. When necessary, we will further optimize the design of our InP & GaSb laser chips to meet our customers' specific optical and electrical performance needs. Diodes, bars and packages are tested to meet customer and market performance demands. Typical results and packaging options are shown. Contact SemiNex for additional details or to discuss your specific requirements.

SemiNex Corporation • 153 Andover Street, Suite 201, Danvers, MA 01923 • 978-326-7700 • sales@seminex.com

Individual. Innovative. Exceptional.


Distributed by IMM Photonics GmbH | imm-photonics.de | phone +49 89 321412-57 | sales@imm-photonics.de

High Power 14-Pin DFB Butterfly Fiber Module

SemiNex CORPORATION

Specification

14BF-453



Optical	Symbol	Typ.	Units
Center Wavelength	λ_c	1550	nm (±5 nm)
Output Power	P_{out}	100	mW
Linewidth	Δf	300	kHz
Side Mode Suppression Ratio	SMSR	55	dB
Relative Intensity Noise	RIN	-150	dBc/Hz
Electrical	**Symbol**		**Units**
Power Conversion Eff.	H	20	%
Operating Voltage	V_{op}	1.5	V
Operating Current	I_{op}	500	mA
Threshold Current	I_{TH}	60	mA
Fiber Package	**Symbol**		**Units**
Fiber Core		8	µm
Fiber Type		900µm jacket	
Connector Type		FC / APC	
Fiber Length		1	m
Pinout Type		Type 1	
Thermistor			
Thermistor Constant	β	3930	β
Thermistor Resistance	R	10	K ohm
Voltage (TEC) – Typ, Max	V_{TEC}	2, 8.2	V
Current (TEC) – Typ, Max	I_{TEC}	0.3, 2.6	A
		Range	
Temperature Coefficient		0.1	nm/°C
Operating Temp.**		-20 to 75	°C
Storage Temp.		-40 to 85	°C

Specified values are rated at a constant heat sink temperature of 20°C.
**High temperature operation will reduce performance and MTTF.
Unless otherwise indicated all values are nominal.

SemiNex Corporation • 153 Andover Street, Suite 201, Danvers, MA 01923 • 978-326-7700 • sales@seminex.com


WARNING - FIBER HANDLING
• Do NOT bend the fiber tighter than 26 mm radius during installation or handling.
• Do NOT bend the fiber tighter than 52 mm radius during normal operation or long-term use.
• Exceeding these limits may cause permanent fiber damage and increased optical loss.

Individual. Innovative. Exceptional.

Distributed by IMM Photonics GmbH | imm-photonics.de | phone +49 89 321412-57 | sales@imm-photonics.de


High Power 14-Pin DFB Butterfly Fiber Module

SemiNex DFB Butterfly 14BF-453




Graphs & Data

Typical DFB Butterfly L-I-V Characteristics



Typical DFB Butterfly Output Spectrum





SemiNex Corporation • 153 Andover Street, Suite 201, Danvers, MA 01923 • 978-326-7700 • sales@seminex.com

High Power 14-Pin
DFB Butterfly Fiber Module

SemiNex CORPORATION


Mechanical Drawing





PINOUT

1. TEC (+)	14. TEC (-)
2. THERMISTOR	13. CASE
3. PD (+)	12. N/C
4. PD (-)	11. LD CATHODE (-)
5. THERMISTOR	10. LD ANODE (+)
6. N/C	9. N/C
7. N/C	8. N/C



All statements, technical information and recommendations related to the product herein are based upon information believed to be reliable or accurate. The accuracy or completeness herein is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its application. SemiNex Corporation reserves the right to change at any time without notice the design, specification, deduction, fit or form of its described herein, including withdrawal at any time of a product offered for sale herein. Users are encouraged to visit www.seminex.com for the latest data. SemiNex Corporation makes no representations that the products herein are free from any intellectual property claims of others. Please contact SemiNex for more information. 2024 SemiNex Corporation

