
IMM photonics

1310nm DM LASER


EP1310-DM-B

eblanaphotonics




SUPERIOR PERFORMANCE

Eblana Photonics EP1310-DM-B laser, available in the 1300-1310nm range, is designed for use in various comms and sensing applications, including FTTX, PON and datacomms systems. Eblana's Discrete-Mode (DM) technology enables tunable single-mode operation with no mode-hops, at a competitive price.



Typical optical spectrum at 25° C



Output power as a function of bias current

ELECTRO-OPTICAL CHARACTERISTICS* (T_{SUB} = 25° C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Available Wavelength Range	λ	1300	1305	1320	nm
Wavelength Tolerance	λ_{spec}	λ -2	λ	λ +2	nm
Side Mode Supression Ratio	SMSR	30	40	-	dB
Threshold Current	I_{th}	-	10	15	mA
Output Power in fiber	P_f	9	14	-	mW
Optical linewidth	Δf	-	2	-	MHz
Temperature Tuning Coefficient	T_λ	-	0.1	-	nm/°C
Current Tuning Coefficient	I_λ	-	12	-	pm/mA
Slope Efficiency	SE	0.13	0.2	-	mW/mA
Thermistor Resistance	R_T	9.5	10	10.5	kΩ
Beta coefficient (85°C/25°C)	B	-	3930	-	K

*CW bias unless otherwise stated

©Eblana Photonics Series 1310-DM-B Rev 1.1

eblanaphotonics

www.eblanaphotonics.com
Sales@eblanaphotonics.com
Dublin, Ireland

Individual. Innovative. Exceptional.

Distributed by IMM Photonics GmbH | imm-photonics.de | phone +49 89 321412-57 | sales@imm-photonics.de

IMM photonics


ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN	MAX	UNIT
Forward Current	I_f	-	120	mA
Forward Voltage	V_f	-	2	V
TEC Current	I_{TEC}	-	1.2	A
Reverse Voltage LD	V_r	-	2	V
Reverse Voltage PD	V_{rev}	-	20	V
Case Temperature*	T_{Case}	-20	65	°C
Storage Temperature	$T_{storage}$	-40	85	°C


*For T_{sub} < 25°C, Max Case Temperature should be derated to $T_{Case,Max} = T_{sub} + 40°C$

PACKAGING

The EP1310-DM-B product series is offered in a 14-pin Butterfly package - Inquire for other packaging options. The standard package pinout is shown below, variations may be requested.



14-pin butterfly schematic



Standard "Pinout 01" option

HOW TO ORDER

Construct your part number using the following example and email your order to sales@eblanaphotonics.com, or call +353 1 675 3220.

EP1310 – 0 – DM – B01 – FA

- EP1310 – 0: Wavelength Band
- DM: Single Mode
- B01: Package Description: B = 14 pin butterfly, 01 = pinout
- FA: Connector/Fiber: FA = FC/APC (SMF), FM = FC/APC (PM)

Laser Safety

This is a Class 3R Laser Product as defined by International Standard IEC 60825-1,Edition 3. Invisible Laser radiation is emitted from the end of the fiber or connector. Avoid direct eye exposure to the beam. Laser safety labels are not attached to the module due to space limitations but instead are affixed to the outside of the shipping carton.

©Elbana Photonics 2022. Eblana Photonics Reserves the right to amend this document at any time, without prior warning. ©Eblana Photonics Series 1310-DM-B Rev 1.1

eblanaphotonics

www.eblanaphotonics.com
Sales@eblanaphotonics.com
Dublin, Ireland

Individual. Innovative. Exceptional.

Distributed by IMM Photonics GmbH | imm-photonics.de | phone +49 89 321412-57 | sales@imm-photonics.de