IMM photonics

1550nm DM LASER


EP1550-DM-TP39

eblanaphotonics




ADVANCED METHANE SENSING

Eblana Photonics EP1550-0-DM-B laser diode, available in the 1533-1560 nm range, is the perfect choice for telecoms applications and LIDAR. Eblana's Discrete-Mode (DM) technology platform enables DFB-like performance at a more competitive price.



Optical Spectrum at 25°C



Output power as a function of bias current

ELECTRO-OPTICAL CHARACTERISTICS (T_{SUB} = 25° C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Available Wavelength Range	λ	1533	1550	1560	nm
Wavelength Tolerance	λ_{spec}	λ -1	λ	λ +1	nm
Side Mode Supression Ratio	SMSR	35	40	-	dB
Threshold Current	I_{th}	-	12	18	mA
Output Power*	P_f	6.5	10	-	mW
Optical linewidth	Δf	-	800	-	kHz
Temperature Tuning Coefficient	T_λ	-	0.1	-	nm/°C
Current Tuning Coefficient	I_λ	-	20	-	pm/mA
Slope Efficiency	SE	0.1	0.15	-	mW/mA
Thermistor Resistance	R_T	9.7	10	10.3	kΩ
Beta Coefficient (85C/25C)	B	-	3930	-	K
Beam divergence - perpendicular	$\theta\perp$	-	28	-	degrees
Beam divergence - parallel	$\theta\parallel$	-	25	-	degrees

*At typical operating current of 80mA

eblanaphotonics

www.eblanaphotonics.com
Sales@eblanaphotonics.com
Dublin, Ireland

Individual. Innovative. Exceptional.


Distributed by IMM Photonics GmbH | imm-photonics.de | phone +49 89 321412-57 | sales@imm-photonics.de

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN	MAX	UNIT
Forward Current	I_f	-	120	mA
Forward Voltage	V_f	-	2	V
TEC Current	I_{TEC}	-	0.7	A
Reverse Voltage LD	V_r	-	2.0	V
Case Temperature	T_{Case}	-20	65	°C
Storage Temperature	$T_{storage}$	-40	85	°C

PACKAGING

The EP1550-DM-TP39 product series is offered in an industry-standard TO39 package - Inquire for other packaging options. The standard package pinout is shown below, variations may be requested.



TO39 schematic - outside bottom view

PIN NO	DESCRIPTION
1	TEC+
2	LD+
3	Thermistor
4	Thermistor
5	LD-
6	TEC-

Standard "Pinout 01" option

HOW TO ORDER

Construct your part number using the following example and email your order to sales@eblanaphotonics.com, or call +353 1 675 3220.

EP1550 - 0 - DM - TP39 - 01

- EP1550 - 0: Wavelength Band
- DM: Single Mode
- TP39: Package Description: TP39 = TO39 with TEC
- 01: Pinout 01

Laser Safety

This is a Class 3R Laser Product as defined by International Standard IEC 60825-1,Edition 2. Invisible Laser radiation is emitted from the end of the fiber or connector. Avoid direct eye exposure to the beam. Laser safety labels are not attached to the module due to space limitations but instead are affixed to the outside of the shipping carton.

©Eblana Photonics 2021. Eblana Photonics Reserves the right to amend this document at any time, without prior warning. ©Eblana Photonics Series 1550-DM-TP39 Rev 1.0

eblanaphotonics

www.eblanaphotonics.com
Sales@eblanaphotonics.com
Dublin, Ireland

Individual. Innovative. Exceptional.

Distributed by IMM Photonics GmbH | imm-photonics.de | phone +49 89 321412-57 | sales@imm-photonics.de