IMM photonics

2122nm DM LASER


EP2122-DM-TP39 - Preliminary

eblanaphotonics




SUPERIOR H2 SENSING

Eblana Photonics EP2122-DM-TP39 laser diode has been developed for precision sensing of Hydrogen in the mid-IR wavelength region. Eblana's Discrete-Mode (DM) technology enables excellent SMSR and tuning performance at a highly competitive price



Representative optical Spectrum at 25°C



Output power as a function of bias current

ELECTRO-OPTICAL CHARACTERISTICS* (T_{SUB} = 25° C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Available Wavelength Range	λ	2120	2121.8	2150	nm
Side Mode Supression Ratio	SMSR	30	40	-	dB
Threshold Current	I_{th}	-	25	-	mA
Output power*	P_f	-	4	-	mW
Temperature Tuning Coefficient	T_λ	-	0.2	-	nm/°C
Current Tuning Coefficient	I_λ	-	20	-	pm/mA
Slope Efficiency	SE	-	0.07	-	mW/mA
Thermistor Resistance	R_T	9.7	10	10.3	kΩ
Beta Coefficient (85C/25C)	B	-	3930	-	K
Beam divergence - perpendicular	$\vartheta\perp$	-	40	-	degrees
Beam divergence - parallel	$\vartheta\parallel$	-	20	-	degrees

*At typical operating current of 80mA

eblanaphotonics

www.eblanaphotonics.com
Sales@eblanaphotonics.com
Dublin, Ireland

Individual. Innovative. Exceptional.


Distributed by IMM Photonics GmbH | imm-photonics.de | phone +49 89 321412-57 | sales@imm-photonics.de

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN	MAX	UNIT
Forward Current	I_f	-	120	mA
Forward Voltage	V_f	-	1.5	V
TEC Current	I_{TEC}	-	0.7	A
Reverse Voltage LD	V_r	-	2	V
Case Temperature*	T_{Case}	-20	65	°C
Storage Temperature	$T_{storage}$	-40	85	°C

PACKAGING

The EP2122-DM-TP39 product series is offered in an industry standard TO39 package - Inquire for other packaging options. The standard package pinout is shown below, variations may be requested.




TO39 schematic - outside bottom view

PIN NO	DESCRIPTION
1	TEC+
2	LD+
3	Thermistor
4	Thermistor
5	LD-
6	TEC-

Standard "Pinout 01" option

HOW TO ORDER

Construct your part number using the following example and email your order to sales@eblanaphotonics.com, or call +353 1 675 3220.





Laser Safety

This is a Class 3R Laser Product as defined by International Standard IEC 60825-1,Edition 2. Invisible Laser radiation is emitted from the end of the fiber or connector. Avoid direct eye exposure to the beam. Laser safety labels are not attached to the module due to space limitations but instead are affixed to the outside of the shipping carton.

©Elbana Photonics 2024. Eblana Photonics Reserves the right to amend this document at any time, without prior warning. ©Eblana Photonics Series 2122-DM-TP39 Rev 0.1

eblanaphotonics

www.eblanaphotonics.com
Sales@eblanaphotonics.com
Dublin, Ireland