
IMM photonics

760nm DM LASER


EP760-DM-TP39

eblanaphotonics




ADVANCED O_2 DETECTION

Eblana Photonics EP760-DM laser diode is the perfect tool for TDLAS-based O_2 sensing. Eblana's patented Discrete-Mode (DM) technology is used to design a cost effective, highly coherent and stable single mode laser.



Representative optical Spectrum at 25°C



Representative LIV plot

ELECTRO-OPTICAL CHARACTERISTICS (T_{SUB} = 25° C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Centre Wavelength (25°C, 80mA)	λ	759	760-761	764	nm
Tuning Range (without Mode Hops)*	λ_{tune}	0.25	0.5	-	nm
Side Mode Supression Ratio	SMSR	30	35	-	dB
Threshold Current	I_{th}	-	35	-	mA
Output Power	P_f	-	15	-	mW
Temperature Tuning Coefficient	T_λ	-	0.06	-	nm/°C
Current Tuning Coefficient	I_λ	-	12	-	pm/mA
Slope Efficiency	SE	-	0.4	-	mW/mA
Thermistor Resistance	R_T	9.7	10	10.3	kΩ
Beta Coefficient (25°C/85°C)	Beta	-	3930	-	K
Beam divergence - perpendicular	$\theta\perp$	-	20	-	degrees
Beam divergence - parallel	$\theta\parallel$	-	10	-	degrees

*Tuning range is defined to be within the operating temperature range of the laser (20 – 40C)

eblanaphotonics

www.eblanaphotonics.com
Sales@eblanaphotonics.com
Dublin, Ireland

Individual. Innovative. Exceptional.


Distributed by IMM Photonics GmbH | imm-photonics.de | phone +49 89 321412-57 | sales@imm-photonics.de

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN	MAX	UNIT
Forward Current	I_f	-	100	mA
Forward Voltage	V_f	-	2.5	V
TEC Current	I_{TEC}	-	0.7	A
Reverse Voltage LD	V_r	-	2.0	V
Case Temperature*	T_{Case}	-20	65	°C
Laser Operating Temperature	T_{Sub}	20	40	°C
Storage Temperature	$T_{storage}$	-40	85	°C

PACKAGING

The EP760-DM-TP39 product series is offered in an industry-standard TO39 package - Inquire for other packaging options. The standard package pinout is shown below, variations may be requested.




TO39 schematic - outside bottom view

PIN NO	DESCRIPTION
1	TEC+
2	LD+
3	Thermistor
4	Thermistor
5	LD-
6	TEC-

Standard "Pinout 01" option

HOW TO ORDER

Construct your part number using the following example and email your order to sales@eblanaphotonics.com, or call +353 1 675 3220.





Laser Safety

This is a Class 3R Laser Product as defined by International Standard IEC 60825-1,Edition 2. Invisible Laser radiation is emitted from the end of the fiber or connector. Avoid direct eye exposure to the beam. Laser safety labels are not attached to the module due to space limitations but instead are affixed to the outside of the shipping carton.

©Elbana Photonics 2021. Eblana Photonics Reserves the right to amend this document at any time, without prior warning. ©Elbana Photonics Series 760-DM-TP39 Rev 2.1

eblanaphotonics

www.eblanaphotonics.com
Sales@eblanaphotonics.com
Dublin, Ireland

Individual. Innovative. Exceptional.

Distributed by IMM Photonics GmbH | imm-photonics.de | phone +49 89 321412-57 | sales@imm-photonics.de